

ASSEMBLING THE FIXTURE

ITEM #29580/2

1. Fasten mounting strip onto wall outlet box using two outlet box screws.
2. Connect the wires from the fixture to the power supply wires from outlet box.
 - d) Twist together white wire from the fixture with white wire from outlet box. Cover with wire connectors.
 - e) Twist together black wire from the fixture with black wire from outlet box. Cover with wire connectors.
 - f) Wrap the ground wires from the fixture and the outlet box around the green ground screw located on the mounting strip. Tighten the green ground screw to the mounting strip.
3. Thread nipple into center hole of mounting strip. Secure with lock washer and hex nut. The nipple should be long enough to protrude out the canopy when mounted.
4. Pass canopy through the nipple. Screw the cap nut onto the protruding nipple on mounting strip until the fixture body is held firmly to the wall.
5. Unscrew the socket rings from sockets.
6. Carefully unpack the glass shades from the box. Set the glass shades onto the sockets, then secure with socket rings.
7. Install the bulb (not included) into socket. Do not use greater than 60-watt bulb.

NOTE: Carefully remove the fixture from the carton. Check that all parts shown in package parts 1 is included.

Be careful not to misplace any of the screws or wire connectors which are needed for installing the fixture.

Package parts 1

Description	No. Of Pieces	Description	No. Of Pieces
Cap nut	1	Nipple	1
Outlet Box Screw	2	Mounting Strip	1
Wire Connectors	2	Green Ground Screw	1
Washer	1	Hex Nut	1
Glass	2		

