



# ASSEMBLY INSTRUCTION

ITEM#31570/1

1. Place the flat side of bracket against the wall at the desired installation location: mark the location of the two mounting holes with pencil. Drill a small hole at each mark and inset the anchors by taping lighting with a hammer.
2. Fasten bracket onto wall outlet box using two screws .
3. Screw 2 wood screw through hole of bracket into anchors of wall.
4. Connect the wires from the fixture to the power supply wires outlet box.
  - A. Twist together white wire from the fixture with white wire from outlet box. Cover with wire connectors.
  - B. Twist together black wire from the fixture with black wire from outlet box. Cover with wire connectors.
  - C. Wrap the ground wire from the fixture around the green ground screw located on the mounting strip. Tighten the green ground screw to the mounting strip.
5. Pass canopy through the support screws of mounting strip. Tighten cap nut onto the protruding support screws on mounting strip until the fixture body is held firmly to the wall.
6. Carefully unpack the glass shade from the box. Set the glass shade onto plate fencing.
7. Install the bulb (not included) into socket. Do not use greater than 60-watt bulb.

**NOTE:** Carefully remove the fixture from the carton. Check that all parts shown in package parts 1 and parts 2 are included. Be carefully not to misplace any of the screws or wire connectors, which are needed for installing the fixture.

## PACKAGE PART

Wire Connectors	2	Glass	1
Support Screw	4		
Green Ground Screw	1		
Outlet Box Screw	2		
Wood screw	2		
Anchor	2		

