



INSTALLATION INSTRUCTIONS

FOR Model: 75539-14

WARNING! SHUT POWER OFF AT FUSE OR CIRCUIT BREAKER.

HANGING THE FIXTURE(Fig.1)

1. Shut off the power at the circuit breaker and remove old fixture, including the crossbar.
2. Carefully unpack your new fixture and lay out all the parts on a clear area. Take care not to lose any small parts necessary for installation.
3. Install bulb. (Type B, not supplied.)
4. Put the glass lens(B) on the fixture(A).
5. Screw the center pipe(C) on the bracket and firm it using the hex nut.
6. Adjust the top hex nut and the flat washer(D) to the right position to protect the glass not to be broke by the extreme force from the top finial(G).
7. Attach the Top Cover(E) on the fixture and firm it using the top finial(G) and rubber washer(F).
8. Mount the metal post base(I) using the self tapping screw(J) and the plastic bolt(H).
9. Connecting the wires(Fig.2):

Connect the black wire from the fixture to the black house (hot) wire. Connect the white wire from the fixture to the white (neutral) house wire. Make sure all wire nuts are secured. You may wrap the connections with electrical tape. If your outlet has a ground wire (green or bare copper), connect fixture's ground wire to it. Otherwise, connect fixture's ground wire directly to the mounting bar using the green screw provided. Tuck the wire connections neatly into the junction box.

10. Place the post Fitter to the metal base, and then secure with the 3 mounting screws(K).
11. Turn on the power at fuse or circuit box.

DO NOT EXCEED THE MAXIMUM WATTAFE RATING!

Your installation is now complete. Return power to the junction box and test the fixture.

